

# TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- BOOTTOPPING

REFERENCE:- G/100/---

COLOUR:- LIMITED RANGE

FINISH:- GLOSS

TYPE:- MODIFIED LONG OIL ALKYD

TYPICAL SG:- 1.15 AT 20°C

TYPICAL VISCOSITY:- 4.5 POISE AT 25°C

TYPICAL TOTAL SOLIDS:- 62% BY WEIGHT  
44% BY VOLUME

FLASH POINT:- ABOVE 32°C

RECOMMENDED THINNERS:- WHITE SPIRIT

APPLICATION:- BY BRUSH,ROLLER OR SPRAY

\*COVERAGE GUIDE:- 12 SQ. METRES/LITRE

\*DRYING TIME:- SURFACE DRY - 4 HOURS  
THROUGH DRY -12 HOURS

USES:- AS A MARINE BOOTTOPPING

HEALTH & SAFETY:- SEE SHEET HSD 'A'

\*BY BRUSH TO A DRIED FILM THICKNESS OF 34-40 MICRONS AT 20°C.

VOC:- > 400 g/litre DEPENDANT ON  
COLOUR

Issued October 2004

## **Teamac® Paints**

**MANUFACTURERS OF DECORATIVE, MARINE AND INDUSTRIAL  
COATINGS**

Teal & Mackrill Limited,  
Lockwood Street, HULL. HU2 OHN  
Telephone: 01482-320194 Fax: 01482-219266