

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- ANTIFOULING "D"

REFERENCE:- C/258/65

COLOUR:- RED

FINISH:- SEMI-GLOSS

TYPE:- MODIFIED OIL BASED

TYPICAL SG:- 1.60 AT 20°C

TYPICAL VISCOSITY:- 4.5 POISE AT 25°C

TYPICAL TOTAL SOLIDS:- 79.5% BY WEIGHT

FLASH POINT:- 38°C

RECOMMENDED THINNERS:- V/607/17

RECOMMENDED APPLICATION:- BY BRUSH, ROLLER OR SPRAY

*COVERAGE GUIDE:- 10 SQ. METRES/LITRE

*DRYING TIME:- SURFACE DRY - 3 HOURS
THROUGH DRY -18 HOURS

USES:- AS A COATING TO DISCOURAGE
FOULANT FORMATION ON BOAT
HULLS AND MARINE
STRUCTURES

HEALTH & SAFETY:- SEE SHEET HSD 'K6' AND SPECIAL LEAFLET
H.S.E. APPROVAL NO. 6418

*BY BRUSH TO A DRIED FILM THICKNESS OF 30-35 MICRONS AT 20°C.

C/258/65 ANTIFOULING D

Teamac® Paints

MANUFACTURERS OF DECORATIVE, MARINE AND INDUSTRIAL
COATINGS

Teal & Mackrill Limited,
Lockwood Street, HULL. HU2 OHN
Telephone: 01482-320194 Fax: 01482-219266