

# TECHNICAL HEALTH AND DATA SHEET

PRODUCT:- ZINC RICH PRIMER

REFERENCE:- P/201/252

COLOUR:- GREY

TYPE:- MODIFIED CHLORINATED  
RUBBER

TYPICAL SG:- 2.9

TYPICAL VISCOSITY:- 8.0 POISE

TYPICAL TOTAL SOLIDS:- 87.3% WEIGHT/WEIGHT  
58.9% VOLUME/VOLUME

FLASH POINT:- ABOVE 32°C

RECOMMENDED THINNERS:- V/607/15 OR V/607/16

APPLICATION:- BRUSH OR AIRLESS SPRAY

\*COVERAGE GUIDE:- 8 SQ. METRES/LITRE

\*DRYING TIME:- SURFACE DRY -1/2 HOUR  
THROUGH DRY -8 HOURS

HEALTH & SAFETY:- SEE SHEET HSD 'K'

\*BY BRUSH TO A DRIED FILM THICKNESS OF 20-25 MICRONS AT 20°C.

**COO-VAR**

PAINTS, PRIMERS & SPECIALISED COATINGS

Ellenshaw Works, Lockwood Street, HULL. HU2 OHN  
Telephone : 01482-328053 Fax: 01482-219266